



MICROCOPY RESOLUTION TEST CHART NATIONAL BUREAU OF STANDARDS-1963-A



M-4133484

OCT 12 1983

83 10 04 212

DTIC FILE COPY

_Ł

DISTRIBUTED WIENER-POISSON CONTROL

Ву

Howard Weiner

TECHNICAL REPORT NO. 325

September 16, 1982

Prepared Under Contract
N00014-76-C-0475 (NR-042-267)
For the Office of Naval Research

Herbert Solomon, Project Director

Reproduction in Whole or in Part is Permitted for any Purpose of the United States Government



DEPARTMENT OF STATISTICS STANFORD UNIVERSITY STANFORD, CALIFORNIA

Accession For			
NTIS	GRA&I	X	
DTIC	TAB	7	
Unannounced 🔲			
Justification			
By Dist:	ribution/		
Availability Codes			
	Avail and	/or	
Dist	Special		
A			

Distributed Wiener-Poisson Control

by Howard Weiner

University of California, Davis and Stanford University

1. Introduction. Let W(t), $t \ge 0$, W(0) = 0 be a standard Wiener process, independent of N(t), $t \ge 0$, W(0) = 0 a Poisson process with (constant) unit jumps, and $EN(t) = \lambda t$, $t \ge 0$. Let their signs fields be $Y(t) = \sigma(W(s), 0 \le s \le t)$ and $G(t) = \sigma(N(s), 0 \le s \le t)$. Let g(y) be a function and L(g(y)) a differential operator on g, for example, $L(g(y)) = a(y) \frac{\lambda}{\partial y} g(y) + d(y) \frac{\lambda}{\partial y} g(y) + c(y)g(y).$ Let X(t,y) be a stochastic process depending on $t \ge 0$ and a parameter y, such that $(for \frac{\lambda X}{\partial t} = X_t)$,

(1.1)
$$X_{t}(t,y) = L(X(t,y)) + u(X(t,y),y) + \frac{dN(t)}{dt} + \frac{dN(t)}{dt}$$

$$X(0,y) = g(y) = x.$$

with $\frac{dW(t)}{dt}$ white noise, $\frac{dN(t)}{dt}$ incremental Poisson jump process and where u(X(t,y),y) is measurable with respect to $\sigma(F(t) \cup G(t))$ (i.e. u is non-anticipative) and satisfies, for A a constant, and B>0 a constant,

$$(1.2) |u-A| \leq B,$$

sl1 $0 \le t \le T$, $0 < T \le \alpha$ a constant. The cost function for a given u satisfying (1.2) is, for $\alpha > 0$ s constant,

(1.3)
$$J(u,y) = \int_0^T e^{-\alpha s} E(X^2(u,s)) ds.$$

The object is to characterize the optimal u for which J is minimized. The cases $T < \omega$ and $T = \omega$ are treated separately. The method employs a suitable Bellman equation, a maximum principle for parabolic partial differential-difference equations and the Ito rule. The method follows [4].

2. Finite Interval Control.

Let T < -. Define, for $0 \le t \le T$,

(2.1)
$$V = V(x,t,y) = \inf_{|u-A| \le B} \int_0^t e^{-\alpha s} E(X^2(s,y)) ds$$

and X(0,y) = g(y) = x. By writing $\int_0^t u \int_0^t + \int_h^{t+h} - \int_t^t$, heuristic arguments ([2], pp. 179-180) yield a Bellman equation

(2.2)
$$|x^{2} + \inf_{|u-A| \leq B} (uV_{x}) + L(g(y))V_{x} + \frac{1}{2}J_{xx} - \alpha V - V_{t}$$

$$+ \lambda(V(x+1,t,y) - V(x,t,y)) = 0,$$

with u = u(x).

On heuristic grounds, a solution to (2.2) is sought such that

(2.3)
$$x^{2} + [(A-B) + L(g(y))] V_{x} + \frac{1}{2} V_{xx} - \alpha V - V_{t} + \lambda (V(x+1,t,y) - V(x,t,y)) = 0$$
 for $V_{x} > 0$, $x > b(t,y)$

and

(2.4)
$$x^{2} + [(A+B) + L(g(y))]V_{x} + \frac{1}{2}V_{xx} - gV - V_{t} + \lambda(V(x+1,t,y) - V(x,t,y)) = 0$$
for $V_{x} < 0$, $x < b(t,y)$

The object is to characterize the optimal u for which J is minimized. The cases $T < \omega$ and $T = \omega$ are treated separately. The method employs a suitable Bellman equation, a maximum principle for parabolic partial differential-difference equations and the Ito rule. The method follows [4].

2. Finite Interval Control.

Let T < -. Define, for $0 \le t \le T$,

(2.1)
$$V = V(x,t,y) = \inf_{|u-A| \le B} \int_0^t e^{-\alpha s} E(X^2(s,y)) ds$$

and X(0,y) = g(y) = x. By writing $\int_0^t \int_0^t + \int_0^{t+h} - \int_t^{t+h}$, heuristic arguments ([2], pp. 179-180) yield a Bellman equation

(2.2)
$$|| \mathbf{x}^2 + \inf_{|\mathbf{u} - \mathbf{A}| \le B} (\mathbf{u}^{\nabla}_{\mathbf{X}}) + L(\mathbf{g}(\mathbf{y}))^{\nabla}_{\mathbf{X}} + \frac{1}{2} \mathcal{I}_{\mathbf{X}\mathbf{X}} - \alpha^{\nabla} - \nabla_{\mathbf{t}} + \lambda (\nabla(\mathbf{x} + 1, \mathbf{t}, \mathbf{y}) - \nabla(\mathbf{x}, \mathbf{t}, \mathbf{y})) = 0,$$

with u = u(x).

On heuristic grounds, a solution to (2.2) is sought such that

(2.3)
$$x^{2} + [(A-B) + L(g(y))]V_{x} + \frac{1}{2}V_{xx} - e^{V-V}t + \lambda(V(x+1,t,y) - V(x,t,y)) = 0$$
 for $V_{x} > 0$, $x > b(t,y)$

and

(2.4)
$$x^{2} + [(A+B) + L(g(y))]V_{x} + \frac{1}{2}V_{xx} - \alpha V - V_{t} + \lambda (V(x+1,t,y) - V(x,t,y)) = 0$$
 for $V_{x} < 0$, $x < b(t,y)$

where b(t,y) is obtained from the following conditions, letting $V = V_1$ in (2.3) and $V = V_2$ in (2.4) for $0 \le t \le T$, all y:

$$V_1(b(t,y),t,y) = V_2(b(t,y),t,y)$$

$$V_{1,x}(b(t,y),t,y) = V_{2,x}(b(t,y),t,y) = 0$$

$$(2.5) V_1(x,0,y) = V_2(x,0,y) = 0.$$

(2.5a)
$$V_{1,xx}(b(t,y),t,y) \ge 0$$
.

For R constant, denote

(2.6)
$$J(x,t,y,R) = \int_0^t e^{-cy^2} E((R+L(g(y))s + W(s) + N(s) + x)^2 ds.$$

A direct computation verifies that J(x,t,y,A-B) is a particular solution to (2.3) and J(x,t,y,A+B) is a particular solution to (2.4).

Assumption 1. There is a non-zero solution $H_1(x,t,y)$ with $H_1(x,0,y)=0$ to

 $-\alpha H + (A-B + L(g(y))H_{X} + \frac{1}{2}H_{XX} - H_{t} + \frac{1}{2}(H(x+1,t,y) - H(x,t,y)) = 0$ such that

$$H_1(x,t,y) = O(e^{-\beta x})$$

(2.7)
$$H_{1,xx}(x,t,y) = 0(e^{-\delta x})$$

for some $\beta > 0$, $\delta > 0$, all t,y, as $x \to \infty$.

Also, there is a non-zero solution $H_2(x,t,y)$ with $H_2(x,0,y)=0$, to $-gH+(A+B+L(g(y)))H_x+\frac{1}{2}H_{xx}-H_{\xi}$

$$+ \lambda (H(x+1,t,y) - H(x,t,y)) = 0$$

such that

$$H_2(x,t,y) = O(e^{\delta x})$$

(2.8)
$$H_{2,xx}(x,t,y) = O(e^{\lambda x})$$

for some $\delta > 0$, $\lambda > 0$, all t,y, as $x \to -\infty$. One may then write

(2.9)
$$V_1(x,t,y) = J(x,t,y, A-B) + H_1(x,t,y)$$

(2.10)
$$V_2(x,t,y) = J(x,t,y,A+B) + H_2(x,t,y)$$
 and assume $b(t,y)$ is determined from (2.5), (2.9), (2.10). This motivates

Theorem 1 Assume the conditions and results of sections 1,2 hold for $0 < T < \infty$.

The optimal un may be expressed as

(2.11)
$$u_0(X_0(t,y),y) = \begin{cases} A-B & \text{if } X_0(t,y) > b(T-t,y) \\ \\ A+B & \text{if } X_0(t,y) \leq b(T-t,y) \end{cases}$$

where b(t,y) is obtained from (2.5), (2.9)-(2.10) and

(2.12)
$$X_{0t}(t,y) = L(X_0(t,y)) + u_0(X_0(t,y),y) + \frac{dW(t)}{dt} + \frac{dN(t)}{dt}$$
 with $X_0(0,y) = g(y) = x$.

<u>Proof</u> Let $D = V_{XX}$. From (2.3), (2.4) (omitting (t,y) arguments)

(2.13)
$$(\underline{A+B} + L(g(y))) D_{x} + \frac{1}{2} D_{xx} - \alpha D - D_{t} - \lambda D = -2 - \lambda D(x+1)$$
 where the argument on the left side of (2.13) is x.

From (2.6),

(2.14) $J_{xx}(x,t,y, A+B) > 0$. Assumption 1, (2.7)-(2.10), (2.14), imply that

 $(2.15) V_{1,xx}(x,t,y) > 0, for each t,y, as x \to \infty$

and

 $(2.16) \quad \nabla_{2,xx}(x,t,y) > 0, \text{ for each } t,y, \text{ as } x \to -\infty.$

For fixed (t,y), (omitting the fixed arguments (t,y)), suppose there existed a finite number r > b, and a number β , $0 < \beta < 1$ and such that using (2.5a),

(2.17) D(x) < 0, $b < r - \beta < x < r$, D(r) = 0, and

(2.17) D(x) > 0, x > r,

using (2.15). It follows that for $x \ge r-\beta$, the left side of (2.13) is negative. By ([1], Lemma 1, p.34), D cannot have a negative minimum for $x \ge r-\beta$, a contradiction to (2.17), since (2.15) and (2.5a) hold. Hence $D \ge 0$ for $x \ge b$.

For $b-1 \le x < b$, a similar argument using (2.16) and that D(x) > 0 for $b \le x < b + 1$ yields that $D(x) \ge 0$ for $b-1 \le x < b$. Continuing by iteration, D(x) > 0 for x < b, so that $D \ge 0$ for all (x,t,y).

Also, $V_{\chi}(b(t)) = 0$ by (2.5), implying that (2.3),(2.4) (2.9), (2.10) is a solution to the Bellman equation (2.2). To show that u_0 is optimal, define

(2.19) $K(X(t,y),t,y) = V(X(t,y),T-t,y)e^{-\alpha^{t}}$ for 0 < t < T.

Moting that K(X(0,y),0,y) = V(x,T,y) and K(X(T,y),T,y) = 0, the Ito rule yields that ([2], pp. 125-126) for a u and corresponding X(t,y),

$$(2.20) \int_{0}^{T} e^{-\alpha s} X^{2}(s,y)ds - V(x,T,y) = \int_{0}^{T} e^{-\alpha s} (-\alpha V(X(s,y),T-s,y) - V_{L}(X(s,y),T-s,y)) + \inf_{|u-A| \le B} (u(X(s,y),y) - V_{L}(X(s,y),T-s,y)) + \frac{1}{2} V_{XX}(X(s,y),T-s,y) + L(g(y)) V_{L}(X(s,y),T-s,y) + X^{2}(s,y))ds + \int_{0}^{T} e^{-\alpha s} (V(X(s,y),T-s,y)dN(s) + \int_{0}^{T} e^{-\alpha s} V_{L}(X(s,y),T-s,y)dW(s) + \int_{0}^{T} e^{-\alpha s} (u(X(s,y),y)V_{L}(X(s,y),T-s,y) - \inf_{|u-A| \le B} (u(X(s,y),y)V_{L}(X(s,y),T-s,y))dW(s) + \int_{0}^{T} e^{-\alpha s} (u(X(s,y),y)V_{L}(X(s,y),T-s,y)) + \int_{0}^{T} e^{-\alpha s} (u(X(s,y),y)V_{L}(X(s,y),T-s,y)) dW(s) + \int_{0}^{T} e^{-\alpha s} (u(X(s,y),y)V_{L}(X(s,y),T-s,y) dW(s) + \int_{0}^{T} e^{-\alpha s} (u(X(s,y),y)V_{L}(X(s,y),T-s,y) dW(s) + \int_{0}^{T} e^{-\alpha s} (u(X(s,y),x)V_{L}(X(s,y),T-s,y) dW(s) + \int$$

The fourth integral on the right of (2.20) is non-negative. Upon taking expectations of (2.20), the third integral on the right is zero, and one obtains (omitting the arguments from the first and fourth integrals, and combining the first and second integrals, all on the right)

$$(2.21) \int_{0}^{T} e^{-\alpha s} E(X^{2}(s,y)) ds - V(x,T,y) =$$

$$E \int_{0}^{T} e^{-\alpha s} (-\alpha V - V_{t} + \inf_{|u-A| \le B} (uV_{x}) + L(g(y))V_{x} + \frac{1}{2}V_{xx} + X^{2} + \lambda (V(X(s)+1)-V) ds$$

$$+ \chi \int_{0}^{T} e^{-\alpha s} (uV_{x} - \inf_{|u-A| \le B} (uV_{x})) ds.$$

The first integral on the right of (2.21) is zero by (2.2)-(2.4), and

the second integral is non-negative, and is zero for $u = u_0$, $X = X_0$. Hence (2.21) yields that

(2.22)
$$\int_0^T e^{-\alpha s} E(X^2(s,y)) ds \ge V(x,T,y)$$

and

(2.23)
$$\int_0^T e^{-\alpha s} E(X_0^2(s,y)) ds = V(x,T,y),$$

and (2.22), (2.23) imply u_0 is optimal.

3. Infinite Interval Control

Assume the conditions of section 1 hold for $T=\infty$ so that (1.3) is now

(3.1)
$$J(u,y) = \int_0^\infty e^{-cys} E(X^2(s,y)) ds.$$

Define

(3.2)
$$V = V(x,y) = \inf_{[u-A] \le B} \int_0^\infty e^{-\alpha s} E(X^2(s,y)) ds$$

with X(0,y) = g(y) = x.

By writing $\int_0^h = \int_0^h + \int_h^m$, heuristic arguments ([2], pp. 179-180) yield a Bellman equation

On heuristic grounds, a solution to (3.3) is sought such that (omitting the (x,y) arguments)

(3.4)
$$x^2 - \alpha V + \frac{1}{2} V_{xx} + (A-B + L(g(y)))V_x + \lambda (V(x+1,y)-V) = 0$$

for $V_x > 0$, $x > b(y)$

and

(3.5)
$$x^{2} - \alpha V + \frac{1}{2} V_{xx} + (A+B+L(g(y))V_{x} + \lambda(V(x+1,y)-V) = 0$$
for $V_{x} < 0$, $x < b(y)$,

where b(y) is obtained from the following matching conditions, letting $V = V_1$ in (3.4) and $V = V_2$ in (3.5):

$$V_1(b(y),y) = V_2(b(y),y)$$

(3.6)
$$V_{1,x}(b(y),y) = V_{2,x}(b(y),y) = 0$$

(3.6a)
$$V_{1,xx}(b,y),y) \ge 0$$
.

For R constant, denote

(3.7)
$$J(x,y,R) = \int_0^{\infty} e^{-ct^2} E((R+L(g(y)))s + W(s)+N(s)+x)^2 ds.$$

A computation verifies that J(x,y,A-B) is a particular solution to (3.4) and J(x,y,A+B) is a particular solution to (3.5).

Assumption 2. There is a non-zero solution $H_1(x,y)$ to (omitting (x,y) argument)

$$-\alpha H + (A-B + L(g(y)))H_X + \frac{1}{2}H_{XX} + \lambda(H(x+1,y)-H) = 0$$

such that

$$H_1(x,y) = O(e^{-\beta x})$$

(3.8)
$$H_{1,xx}(x,y) = O(e^{-6x})$$

for some $\beta>0$, $\delta>0$, for each y, as $x\to\infty$. Similarly, there is a non-zero solution $H_2(x,y)$ to

$$-\alpha H + (A+B + L(g(y)))H_x + \frac{1}{2}H_{xx} + \lambda(H(x+1,y)-H) = 0$$

such that

$$H_2(x,y) = O(e^{\delta x})$$

(3.9)
$$H_{2,xx}(x,y) = 0(e^{\lambda x})$$

for some $\delta > 0$, $\lambda > 0$, for each y as $x \to -\infty$.

Then one may write

(3.10)
$$V_1(x,y) = J(x,y,A-B) + H_1(x,y)$$

(3.11)
$$V_2(x,y) = J(x,y,A+B) + H_2(x,y)$$

and assume that b(y) is determined from (3.6), (3.10), (3.11). As in Section 2, one then obtains

Theorem 2. Assume that the conditions and results of sections 1,3 hold for $T = \infty$.

The optimal u_1 may be expressed as

(3.12)
$$u_1(X_1(t,y),y) = \begin{cases} A-B & \text{if } X_1(t,y) > b(y) \\ \\ A+B & \text{if } X_1(t,y) \leq b(y) \end{cases}$$

where b(y) is obtained from (3.6), (3.10)-(3.11) and

(3.13)
$$X_{1t}(t,y) = L(X_1(t,y)) + \frac{dW(t)}{dt} + \frac{dN(t)}{dt}.$$
and
$$X_1(0,y) = g(y) = x.$$

Proof. The proof follows that of Theorem 1.
Let D = V_x. From (3.4), (3.5) (omitting (x,y) arguments)

(3.14) $(\underline{A+B} + L(g(y)))D_x + \frac{1}{2}D_{xx} - \alpha D - \lambda D = -2 - \lambda D(x+1)$ where the argument on the left side of (3.14) is x.

From (3.7),

(3.15)
$$J_{xx}(x,y,A+B) > 0.$$

Assumption 2, (3.8)-(3.11), (3.15) imply that

(3.16)
$$V_{1,xx}(x,y) > 0$$
 for each t,y, as $x \to \infty$

and

(3.17)
$$V_{2,xx}(x,y) > 0$$
 for each t,y, as $x \to -\infty$.

By an argument identical to that given in the proof of Theorem 1, using the appropriate maximum principle ([1], Theorem 18, p. 53), it follows that $D(x,y) \ge 0$ for all (x,y). Since $V_x(b(y),y) = 0$

by (3.6), it follows that (3.4), (3.5), (3.10), (3.11) constitute a solution to the Bellman equation (3.3). To show that \mathbf{u}_1 is optimal, define

(3.20)
$$K(X(t,y),y) = V(X(t,y),y)e^{-\alpha^{t}}$$

for $t \ge 0$.

Noting that K(X(0,y),y) = V(x,y), one obtains from the Ito rule ([2], pp. 125-126) for a u and corresponding X(t,y), (omitting (X(s,y),y) arguments on the right side),

(3.21)
$$\int_{0}^{t} e^{-crs} X^{2}(s,y) ds + V(X(t,y),y) e^{-crt} - V(x,y) =$$

$$\int_{0}^{t} e^{-crs} (X^{2}(s,y) - crv + \inf_{|u-A| \le B} (uV_{x}) + L(g(y)) V_{x} + \frac{1}{2} V_{xx}) ds$$

$$+ \int_{0}^{t} e^{-crs} (uV_{x} - \inf_{|u-A| \le B} (uV_{x})) ds$$

$$+ \int_{0}^{t} e^{-crs} (V(X(s,y),s) dN(s)$$

$$+ \int_{0}^{t} e^{-crs} V_{x} dW(s) .$$

The second integral on the right of (3.21) is non-negative. Upon taking expectations in (3.21), the fourth term on the right is zero, and combining the first and third terms on the right yields that

(3.22)
$$\int_0^t e^{-\alpha s} E(X^2(s,y)) ds + E(V(X(t,y),y)) e^{-\alpha t} - V(x,y) =$$

$$E\int_0^t e^{-\alpha s} (X^2(s,y) - \alpha V + \inf_{|u-A| \le B} (uV_x) + L(g(y)) V_x + \frac{1}{2} V_{xx}$$

$$+ \lambda (V(X(s)+1,y) - V) ds$$

 $+ E \int_{0}^{t} e^{-\alpha s} (uV_{x} - \inf_{|u-A| \le B} (uV_{x})) ds.$

By (3.3), the first term on the right of (3.22) is zero.

The second term on the right of (3.22) is non-negative, and is zero for $u = u_1$. By Assumption 2, (3.7)-(3.11), it follows that, for (x,y) fixed, there is a constant D > 0 such that

(3.23) $E(V(X(t,y),y))e^{-ct} \le E(|x|+(|A|+B+|L(g(y)|)t+|W(t)|+N(t))^2e^{-ct}+De^{-ct}$ or

(3.24)
$$E(V(X(t,y),y)e^{-\alpha t} \le C(x,y)t^2e^{-\alpha t}$$

for some positive constant C(x,y).

Letting $t \rightarrow \infty$ in (3.22), by (3.24) one obtains

(3.25)
$$\int_0^\infty e^{-\alpha s} E(X^2(s,y)) ds \ge V(x,y)$$

and

(3.26)
$$\int_0^{\infty} e^{-crs} E(x_1^2(s,y)) ds = V(x,y),$$

so that (3.25), (3.26) imply that u₁ is optimal.

4. Additional Constraints

Gertain additional constraints may be incorporated and treated by these methods. An illustrative example in the case $\,T<\infty$ is the added constraint

(4.1)
$$E(X^2(a)) = C$$

where $0 < a \le T$ and C > 0. This may be handled by adding the condition

(4.2)
$$V_t(x,t,y)|_{t=a} e^{-\alpha a}C$$

to conditions (2.5), and proceeding as before. See [3] for another approach.

REFERENCES

- [1] A. Friedman, <u>Partial Differential Equations of Parabolic Type</u>,

 Prentice-Hall, Inc., Englewood Cliffs, New Jersey, (1964).
- [2] I.I. Gihman and A.V. Skorohod, <u>Controlled Stochastic Processes</u>

 (English Translation), Springer-Verlag, New York, New York, (1979).
- [3] U.G. Haussmann, Some examples of optimal stochastic controls, or:

 the stochastic maximum principle at work, SIAM Review, 23, No.3(1981),

 pp. 292-307.
- [4] I. Karatzas, Optimal discounted linear control of the Wiener process,

 J. Optimization Theory and Applic., 31, (1980), pp. 431-440.

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Date Entered)

REPORT DOCUMENTATION PAGE	READ INSTRUCTIONS BEFORE COMPLETING FORM		
1. REPORT NUMBER 325 A133 PG T ACCESSION NO	1. RECIPIENT'S CATALOG NUMBER		
4. TITLE (and Subtitle)	S. TYPE OF REPORT & PERIOD COVERED		
DISTRIBUTED WIENER-POISSON CONTROL	TECHNICAL REPORT		
	6. PERFORMING ORG, REPORT NUMBER		
7. AUTHOR(a)	B. CONTRACT OR GRANT NUMBER(s)		
Howard Weiner	N00014-76-C-0475		
9. PERFORMING ORGANIZATION NAME AND ADDRESS	10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS		
Department of Statistics Stanford University	NR-042-267		
Stanford, CA 94305			
11. CONTROLLING OFFICE NAME AND ADDRESS	12. REPORT DATE		
Office Of Naval Research	September 16, 1982		
Statistics & Probability Program Code 411sp Arlington, VA 22217	14		
14. MONITORING AGENCY NAME & ADDRESS(II dillerent from Controlling Office)	18. SECURITY CLASS. (of this report)		
·	UNCLASSIFIED		
	15a. DECLASSIFICATION/DOWNGRADING		
16. DISTRIBUTION STATEMENT (of this Report)	<u> </u>		
APPROVED FOR PUBLIC RELEASE: DISTRIBUTION UNLIMITED.			
17. DISTRIBUTION STATEMENT (of the obstract entered in Block 20, if different from Report)			
18. SUPPLEMENTARY NOTES			
19. KEY WORDS (Continue on reverse side if necessary and identity by block number)			
Optimal Wiener-Poisson control; discounted quadratic cost; Bellman equation;			
<pre>partial differential-difference equations; asymmetric bang-bang control;</pre>			
maximum principle, Ito-rule.			
20. ATST RACT (Continue on reverse olde if necessary and identity by block number)			
PLEASE SEE REVERSE SIDE.			

AN ANNANCY APPROXISE (DESERTED

#325

A one-dimensional Wiener plus independent Poisson control problem with state governed by a partial differential equation has integrated discounted quadratic cost function and asymmetric bounds on the control, which is a function of the current state. A Bellman equation and maximum principle for partial differential equations are used to obtain the optimal closed loop control in bang-bang form. The finite and infinite integral quadratic cost functions are treated separately.

\$ 9 3132- 45 314- 2031

